



| NO.1 | |
|---------|--------|
| PART NO | VIGOR |
| 3 | 180±35 |
| 4 | 250±35 |

| NO.2 | |
|---------|--------------|
| PART NO | MATERIAL/QTY |
| S | SUS/1PC |
| D | SUS/2PCS |

| NO.3-NO.4 | |
|-----------|---------------|
| PART NO | NOTE |
| 01~99 | SERIAL NUMBER |

| ITEM | PART NAME | TER'NO. | QTY. | MATERIAL | FINISHING | REMARK |
|------|-----------|---------|------|-----------------|----------------|--------|
| ⑤ | Terminal | --- | 3 | Phosphor Bronze | Plating silver | --- |
| ④ | Contact | --- | 2 | SUS | Plating silver | --- |
| ③ | Base | --- | 1 | Nylon | Black | --- |
| ② | Cover | --- | 1 | SUS | Natural | --- |
| ① | Knob | --- | 1 | Silica gel | Black | --- |

| APPROVALS | | DATE |
|-----------|-----------|-----------|
| DRAWN | J.X.Zhong | 2013/9/13 |

| APPROVALS | | TITLE: | PART NO. | SCALE: | PROJ. |
|----------------|-------|--------------|-------------------|--------|-------|
| CHECKED | | TACT SWITCHS | K2-1812GA-DOOW-00 | 1:1 | |
| APPROVALS | | | | | |
| TOLERANCES ARE | | | | | |
| 30~0.1 | ±0.30 | ANGLE | | | |
| 10~0.30 | ±0.20 | UNIT: mm | | | |
| 5~10 | ±0.15 | DRAWING NO. | | | |
| ~5 | ±0.10 | | | | |

| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. |
|---------|------|-------|--------------|---------|--------|--------|
| | A | | NEW | | | |



ELECTRONICS CO.,LTD